

F Series Semi-Flexible Borescopes



Features & Specifications

Diameter:	0.312" (8mm) to enter cavity of 0.315" (8.1mm) or larger
Flexible Length:	24" (609.6mm)
Minimum Bend Radius:	1.75" (44.5mm)
Illumination:	Battery-operated internal flashlight
Magnification:	20X
Field of View:	60°
Focal Length:	0.20" to 3" (5.1mm to 76.2mm)
Maximum Temperature:	200°F (93°C)
Other Features:	Focusing eyepiece Additional 90° viewing head included Battery handle Stay put sheathing bend & hold Carrying case

Accessories & Options

- FOI-150 Fiberoptic Illuminator with 150W quartz halogen lamp
- FB-6 Fibre Bundle to connect fiberoptic illuminator to the borescope

F Series flexible borescopes are maneuverable through several bends and include a battery-operated internal cold light source. These features make the unit portable and adaptable for many uses such as inspecting the inside of boilers, turbines and compressors, and where viewing around bends or in high-temperature conditions is required. A right-angle viewing attachment is included at no extra charge. The F Series can also be adapted for greater illumination and video viewing.

F Series Ordering Information

Model Number	Flexible Length	Price
F-1	24" (609.6mm)	\$ 1,095.00
Accessories & Options		
FOI-150	150W Fiberoptic Illuminator	\$ 305.00
FB-6	Fibre Bundle	175.00
Q1250	150 Watt 21Volt Lamp for FOI-150	24.90