

### F Series Semi-Flexible Borescopes



#### Features & Specifications

|                      |  |
|----------------------|--|
| Diameter:            | 0.312" (8mm) to enter cavity of 0.315" (8.1mm) or larger   |
| Flexible Length:     | 24" (609.6mm)  |
| Minimum Bend Radius: | 1.75" (44.5mm)   |
| Illumination:        | Battery-operated LED flashlight  |
| Magnification:       | 20X  |
| Field of View:       | 60°  |
| Focal Length:        | 0.20" to 3" (5.1mm to 76.2mm)  |
| Maximum Temperature: | 200°F (93°C)   |
| Other Features:      | Focusing eyepiece<br>Additional 90° viewing head included<br>Battery handle<br>Stay put sheathing bend & hold<br>Carrying case |

F Series flexible borescopes are maneuverable through several bends and include a battery-operated internal cold light source. These features make the unit portable and adaptable for many uses such as inspecting the inside of boilers, turbines and compressors, and where viewing around bends or in high-temperature conditions is required. A right-angle viewing attachment is included at no extra charge. The F Series can also be adapted for greater illumination and video viewing.

#### F Series Ordering Information

| Model Number | Flexible Length |
|--------------|-----------------|
| F-1          | 24" (609.6mm)   |